



EPS-1008

Article number: 211982

PoE Switch, 8x PoE+, 1x RJ45, 1x SFP, 130W, Metal Housing

Mainfeatures

Fast Ethernet: 8x 10/100 Base-TX, IEEE 802.3at

Gigabit Ethernet: 1x 10/100/1000 Base-T, 1x SFP

VLAN, PoE control, Backup/Restore

Port Mirroring, Password protected

Temperature range 0°~45°C

Up to 30W per port, total max. 130W

Web-based Configuration / Management

RSTP/Loop protection, Bandwith control

Status LED: Link/PoE

Specifications

Management	yes
VLAN	yes
Ports	8x 10/100Base-TX, 1x 10/100/1000Base-T, 1x 1000 SFP
Optical connection	Duplex LC System plug
Ethernet interface	10Base-T, 100Base-TX, 1000Base-T
Switch data rate	10Mbps port - 14,880pps, 100Mbps port - 148,880pps, 1000Mbps port - 1,148,880pps
Support standards	IEEE 802.3 10BaseT, IEEE 802.3z 1000BaseSX/LX, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3x Flow Control, IEEE 802.3ad Link Aggregation Control Protocol, IEEE 802.1Q VLAN, IEEE 802.1p Class of Service, IEEE 802.1D Spanning Tree Protocol, IEEE
Supply voltage	100~240VAC
Power over Ethernet	yes
Power over Ethernet	IEEE 802.3at

EPS-1008

Specifications continued

Number PoE ports	8
PoE Power	130 W
Model	housing
Mounting	19" rack
Application	indoor
Power consumption	130W
Temperature range (operation)	0°C ~ +45°C
Blower	yes
Weight	1,8 kg

EPS-1008

Available Accessories

Bild	Art. Nr. / Bezeichnung	Beschreibung
	211978 / EFC-S1310SFP	SFP Modul, Gigabit,10km, Singelmode 1310nm, Duplex LC Connector

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com