



## MEB-62V2812P0B

Article number: 219548

1/2.8" HD Camera, Day&Night, 1920x1080, Infrared, D-WDR, 2,8-12mm, 12VDC, IP66

1/2.8" 2.3 Megapixel progressive scan CMOS sensor

Compact housing for outdoor use

Resolution max. 1920x1080 (Full HD)

Multisignal: HD-TVI, AHD, CVI, Composite selectable

Variofocal 2.8~12mm day&night lens

LSC (Lens shading compensation)

Removable infrared cut filter

3D-DNR noise reduction

Digital Wide Dynamic Range (D-WDR)

Integral motion detection

4x High Power LED

## Specifications

Camera:		Features:	
Camera type	Bullet	OSD function control	OSD camera setup
Sensor size	1/2.8"	Menu languages	German, English, French, Italian, Spanish, Turkish, Dutch, Portugese, Polish, Chinese, Russian
Resolution pixels	1920x1080, 960x576	Privacy zones masking	Areas-ON/OFF switchable
Imager	CMOS, Sony, Sensor IMX322	Mirror function	rotation, mirror, V flip
System	True Day&Night	Digital Noise Reduction (DNR)	yes
Sensitivity	0,3 Lux, at F1.3, 40IRE		
Low speed shutter	yes, automatic		
Manual electronic shutter (MES)	1/25 ~ 1/50.000sec.		
Automatic electronic shutter (ESC)	1/25 ~ 1/50.000sec..		
Wide Dynamic Range (WDR)	D-WDR		
Flickerless function	yes		
Backlight compensation	BLC, HLC		
IR cut filter	switchable		
White balance	ATW, AWB, manual, outdoor, indoor, AWC		
Signal-to-noise ratio	52db		
Video:		Interfaces / Inputs / Outputs:	
Video standard	PAL/NTSC	Video outputs	HD-TVI, AHD, CVI, composite (CVBS)
Signal format	Composite (FBAS), HD-TVI @ 2MP, AHD @ 2MP, CVI @ 2MP	External connections	video (BNC), 12VDC power input, connection cable approx.25cm
Frame rate	25/30fps @ 1920x1080p	Alarm inputs	no
Synchronization	internal	Alarm outputs	no
		Serial interfaces protocols	UTC
Lens:		General:	
Lens type	varifocal	Series	KX-Series
Zoom factor	4x	Dimensions (HxWxD)	78,5x78,5x214mm
Focal length	2,8 - 12 mm	Illumination	infrared, 4x High Power LEDs 850nm
Digital zoom	no	Illumination range	approx. 30m
MOD (Minimum object distance)	0,5 m	Colour (housing)	Pantone Cool Gray 1C
Aperture range (F)	F1,3	Housing	outdoor
Iris control	DC	Housing material	aluminium, plastic
Vertical angle of view	53 - 17 °	Weight	520g
Horizontal angle of view	98 - 31 °	Integrated wall mount	yes
		Power consumption	6.5W
		Mounting	wall mount, ceiling mount
		Protection rating	IP66
		Hidden cable management	yes
		Sunshield	yes
		Supply voltage	12VDC
		Temperature range (operation)	-20°C ~ +50°C
		Text display	supplied
Features:		Scope of delivery:	
Motion detector	yes	Parts supplied	manual, drilling template, bag of screws

## Related Products



PS12DC-11 | SKU: 218653

## Product recommendations



TVA-1201TRA|SKU: 212984



TVA-1201TRP|SKU: 212985



MAM-5ME1001MTA|SKU: 217344



MAM-5MM1001MOA|SKU: 220299



MAM-6ME1012MTA|SKU: 219643

