



IPC-52A0030P0A

Article number: 212716

1/2.8" Network Camera, Day&Night, 1920x1080, WDR, 30x AF Zoom, 4.3-129mm, Indoor

1/2.8" Sony CMOS Sensor	Real time WDR (Wide Dynamic Range) 25/30fps
30x AF Zoom, 4.3-129mm / 16x Digital	Digital Image Stabilisation (DIS)
Full HD 1920x1080 pixels, 1080p@50/60fps	Privacy zones
Compression H.264/MJPEG, Web Casting	Alarm in- and outputs, microSD card slot
Digital Noise Reduction (DNR)	ONVIF conformity
VCA Video Analytic	

Specifications

Camera:		Features:	
Camera type	Zoom Camera	e-PTZ support	yes
Sensor size	1/2.8"	Internal storage	microSDHC card, microSDXC card
Resolution standard	HD 1080p	Menu languages	English, Korean, Chinese, Russian, German, French, Japanese
Imager	CMOS, Sony STARVIS, Sensor IMX291	Privacy zones masking	Areas-ON/OFF switchable
System	True Day&Night	Remote configuration	web browser
Sensitivity	0,35 Lux, 50 IRE, at F1.6	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Low speed shutter	yes, 2x ~ 8x	User interface	Type B (white / blue)
Manual electronic shutter (MES)	1/25 ~ 1/30.000sec	Mirror function	H/V flip
Automatic electronic shutter (ESC)	1/25 ~ 1/30.000sec.	Digital Noise Reduction (DNR)	yes
Wide Dynamic Range (WDR)	WDR 120dB, Real Time WDR 25/30fps	Network:	
Backlight compensation	BLC, HLC	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Day/Night switching	auto, day, night	Interfaces / Inputs / Outputs:	
IR cut filter	switchable	External connections	RJ-45, voltage input, audio input/output, RS-485, alarm output, alarm input, SD card slot, video (BNC)
White balance	automatic, outdoor, manual, fluorescent, Light bulb	Ethernet interface	10Base-T, 100Base-TX
Video:		Alarm inputs	1
Resolution	1920x1080 (16:9), 1280x1024 (5:4), 1280x960 (4:3), 1024x768 (4:3), 1280x720 (16:9), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 640x360 (16:9), 320x240 (4:3)	Alarm outputs	1
Resolution max.	1920x1080	Serial interfaces	RS-485, Ethernet
Stream types	2x H.264, 1x MJPEG multiple	Serial interfaces protocols	Pelco D, Pelco P, Fastrax IIE, Fastrax
Image transmission rate max.	60 fps	General:	
Multicast compliant	yes	Series	SN-Series
Compression standard	H.264, M-JPEG	Dimensions (HxWxD)	88.6x81x142mm
Lens:		Mount	1/4" UNC-20
Lens type	auto focus zoom	Colour (housing)	white
Zoom factor	30x	Housing	indoor
Focal length	4,3 - 129,0 mm	Housing material	aluminium, plastic
Digital zoom	16x	Weight	700g
MOD (Minimum object distance)	1 m	Power consumption	9W
Iris control	DC	Blower	yes
Vertical angle of view	36,4 - 1,29 °	ONVIF	ONVIF Profile S
Horizontal angle of view	61,8 - 2,11 °	Power over Ethernet	IEEE 802.3af
Features:		SDK	upon request
Motion detector	yes	Supply voltage	PoE, 12VDC, 24VAC
Analysis functions	motion detection, tampering protection, trip wire detection with counting and direction detection, Field detection, face detection, Defog	Temperature range (operation)	0°C ~ +50°C
Alarm processing	FTP, E-Mail, HTTP, Boost, microSD card recording	Text display	supplied
Audio	2 Way Audio	Scope of delivery:	
Audio support	yes	Parts supplied	manual, eneo Site Manager
Password protection	yes		

Related Products



VHM/ECLKB-W|SKU: 79676



PS12DC-11|SKU: 218653



WD-30|SKU: 219504

Product recommendations



IAR-75E1024MMA|SKU: 214460



IAM-55E1008MUA|SKU: 214459



IAM-55G1008MMA|SKU: 216129



IAD-55G1004MUA|SKU: 216469



IAD-55G1008MUA|SKU: 216472



IAR-75G1008MMA|SKU: 216473



IAR-75G1016MMA|SKU: 216474



IAR-75G1024MMA|SKU: 216682



eneo Site Manager|SKU: 218218

