



## IPC-55C0000M0A

Article number: 213022

1/1.8" Network Camera, 2592x1944, Day&Night, D-WDR, C/CS, Indoor

1/1.8" 5.0 Megapixel RGB Bayer Array CMOS	VerticalView 90°/270° mode only H.264, HTML5 Playback
Resolution max. 2592x1944	Digital Wide Dynamic Range (D-WDR)
C/CS lens mount, IR cut filter	LDC (Lens Distortion Correction), Defog function
Cross Web Browsing (IE, Safari, Firefox, Chrome)	Slot for Micro SD card
Responsive Web Design, Zero configuration	ONVIF conformity, PoE IEEE802.af
Triple Streaming: 2x H.264, 1x MJPEG	External input for day&night switching

## Specifications

Camera:		Features:	
Camera type	Box	e-PTZ support	yes
Sensor size	1/1.8"	Internal storage	microSDHC card, microSDXC card
Resolution standard	5 Megapixel	Menu languages	French, English, German, Polish, Finnish
Imager	CMOS, Sony STARVIS, Sensor IMX178	Privacy zones masking	Areas-ON/OFF switchable
System	True Day&Night	Remote configuration	web browser
Sensitivity	0,07 Lux, at F1.5, 40IRE	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Low speed shutter	no	User interface	Type A (orange / grey)
Manual electronic shutter (MES)	1/12.5 ~ 1/10.000sec.	Mirror function	mirror, flip
Automatic electronic shutter (ESC)	1/12.5 ~ 1/10.000sec.	Digital Noise Reduction (DNR)	yes
Wide Dynamic Range (WDR)	D-WDR	Network:	
Flickerless function	yes	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Backlight compensation	BLC, HLC	Interfaces / Inputs / Outputs:	
Day/Night switching	auto, day, night, extern (Sensor)	Video outputs	no
IR cut filter	switchable	External connections	RJ-45, audio in/output, alarm in/output, voltage input, micro SD card slot
White balance	ATW-Indoor, ATW-Outdoor, automatic, manual, Light bulb, Flammes, Fluorescent light, Shade, Clear Sky	Ethernet interface	10Base-T, 100Base-TX
		Alarm inputs	1
		Alarm outputs	1
		Serial interfaces	no, Ethernet
Video:		General:	
Resolution	5 Megapixel Modus @ 12,5fps, 2 Megapixel Modus @ 30fps, 3MP Mode @25fps, 2592x1944 (4:3), 2560x1440 (16:9), 2048x1536 (4:3), 1920x1440 (4:3), 1920x1080 (16:9), 1600x1200 (4:3), 1280x960 (4:3), 640x360 (16:9), 1280x720 (16:9), 800x600 (4:3), 640 x 480 VGA, 320x240 (4:3)	Series	KN-Series, eneo Candid Box
Resolution max.	2592x1944	Dimensions (HxWxD)	72x74x89mm
Stream types	2x H.264, 1x MJPEG multiple	Mount	2x 1/4" UNF-20
Image transmission rate max.	30 fps	Colour (housing)	Pantone Cool Gray 1C
Multicast compliant	yes	Housing	indoor
Compression standard	H.264, M-JPEG	Housing material	aluminium
		Weight	300g
		Power consumption	6W
Lens:		Blower	yes
Lens type	lens not included	ONVIF	ONVIF Profile S
Lens mount	CS/C mount	Power over Ethernet	IEEE 802.3af
Digital zoom	16x	SDK	upon request
Iris control	DC	Supply voltage	24VAC, 12VDC, PoE
		Temperature range (operation)	-10°C ~ +50°C
		Text display	supplied
Features:		Scope of delivery:	
Motion detector	yes	Parts supplied	manual, eneo Site Manager, C/CS adapter
Analysis functions	motion detection, tampering protection, trip wire detection with counting and direction detection, Field detection, Defog		
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, Onvif Event Mapping, alarm out		
Audio	2 Way Audio		
Audio support	yes		
Password protection	yes		

## Related Products



VHM/ECLKB-W|SKU: 79676



H04Z03NFDC-MP|SKU: 213619



PS12DC-11|SKU: 218653



WD-30|SKU: 219504

## Product recommendations



IAR-7SE1024MMA|SKU: 214460



IAM-5SE1008MUA|SKU: 214459



IAM-5SG1008MMA|SKU: 216129



IAD-5SG1004MUA|SKU: 216469



IAD-5SG1008MUA|SKU: 216472



IAR-7SG1008MMA|SKU: 216473



IAR-7SG1016MMA|SKU: 216474



IAR-7SG1024MMA|SKU: 216682



eneo Site Manager|SKU: 218218

