

8 Port 10/100 Mbps + 2 Port Giga PoE Switch

PoES-08120+2GI



10/100 Mbps



- Downlink: 4x100Mbps Ports
- Uplink: 2x 1Gbps Port
- 120W (Avg:15W Max 30W per ch)
- Distance: Up to 100 Meter
- Built-in Surge Protection
- Internal Power Supply
- Complies With IEEE802.3af/at
- CCTV mode:
 - Up to 250 meter at 10Mbps
 - Vlan function: no communication among downlink ports
 - Wall Bracket/Anti-Theft Hole Lock(k-slot)/Earthing Connector

Specifications

MODEL	PoES-08120+2GI	
Interface	Downlink Ports	8 x 10/100Mbps
	Uplink Ports	2 x 10/100/1000Mbps
	SFP Ports	No
PoE	PoE Ports	8 (Downlink Ports)
	PoE Standard	IEEE802.3af/at PoE
	PoE Total Power	120W
	Average Power Per Channel	15W
	Maximum Power Per Channel	30W
Data Processing	Backbone Bandwidth	7Gbps
	Buffer Size	1.5Mb
	MAC Address Table	4K
	VLAN	Auto (In CCTV Mode)
Network Media	EIA/TIA-568	100Ω STP (Maximum 100m)
	10BASE-T	UTP Category 3, 4, 5 Cable (Maximum 100m)
	100BASE-TX	UTP Category 5, 5e Cable (Maximum 100m)
	1000BASE-T	UTP Category 5e, 6, 7 Cable (Maximum 100m) [For Uplink Ports Only]
Special	CCTV Mode	Selectable Standard/CCTV Mode
	Surge Protector	Built-In
	Wall Bracket	Optional
	Rack Bracket	No
	K-Slot (Anti Theft)	Available
Power	PoE Status Monitor	No
	Power Supply	100-240VAC
Others	Power Consumption	PoE On: 124W Max. / PoE Off: 4W Max.
	Fan	No
	Dimensions	219.6*105*27.6 mm
	Weight	1.32kg
	Operating Temperature	-0°C-40°C



CCTV Mode Switch



100-240VAC Power Input