



## ISD-59P0010P0A

Article number: 220196

1/1,7" Network Dome, Fix, Day/Night, 3840x2160, H.265, 1,29mm, 360°, IP66

|   |  |
|---|--|
| 1/1.7" Sony STARVIS CMOS-Sensor                                   | Quad Stream (H.264/H.265x3, MJPEGx1)                 |
| 1.29mm fixed lens FishEye camera                                  | Cross Web-Browsing                                   |
| 360° Panorama-, Corridor-, Quad-, Panomorph-View, ceiling or wall | True-WDR (Digital Wide Dynamic Range)                |
| Integration in eneo Center Software                               | Framerate increase on motion detection (Smart Codec) |
| True Day & Night  | IR-LED Illumination integrated                       |
| Resolution max. 4000x3000@20fps                                   | Compact design for indoor application                |

## Specifications

| Camera:                            |  | Features:                      |   |
|------------------------------------|--|--------------------------------|---|
| Camera type                        | Dome   | Remote configuration           | web browser   |
| Resolution standard                | 4K Ultra HD  | Web browser                    | MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited |
| Imager                             | CMOS, Sony STARVIS, Sensor IMX226  | Digital Noise Reduction (DNR)  | yes   |
| System                             | True Day&Night   | Network:                       |   |
| Sensitivity                        | 0,3 Lux, at F2.8   | Network protocols              | TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS   |
| Low speed shutter                  | yes, automatic   | Interfaces / Inputs / Outputs: |   |
| Manual electronic shutter (MES)    | 1~1/20.000sec.   | External connections           | alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.40cm   |
| Automatic electronic shutter (ESC) | 1~1/20.000sec.   | Ethernet interface             | 10Base-T, 100Base-TX  |
| Wide Dynamic Range (WDR)           | WDR 120dB  | Alarm inputs                   | 1   |
| Backlight compensation             | BLC  | Alarm outputs                  | 1   |
| Day/Night switching                | auto, day, night   | Serial interfaces              | Ethernet  |
| IR cut filter                      | switchable   | General:                       |   |
| White balance                      | automatic, fluorescent, manual, outdoor, incandescent  | Series                         | eneo SN-Series  |
| Video:                             |  | Dimensions (HxWxD)             | 58,7x151,4mm  |
| Resolution                         | 4000x3000 (4:3), 3000x3000, 2560x2560,, 2160x2160, 2048x2048, 1280x1280, 640x640, 480x480  | Illumination                   | infrared, 6x LEDs 850nm   |
| Stream types                       | Quad Streaming   | Illumination range             | approx. 10m   |
| Image transmission rate max.       | 30 fps   | Colour (housing)               | white   |
| Compression standard               | H.264, H.265, H.264+, H.265+, M-JPEG   | Housing material               | metal   |
| Lens:                              |  | Weight                         | 750g  |
| Lens type                          | fixed focal length   | Heater                         | no  |
| Focal length                       | 1,29 mm  | Power consumption              | 12.5W @ PoE,, 15W @ VDC12V  |
| Digital zoom                       | yes  | Blower                         | no  |
| MOD (Minimum object distance)      | 0,1 m  | Mounting                       | wall mount, ceiling mount   |
| Horizontal angle of view           | 360 °  | ONVIF                          | ONVIF Profile S   |
| Features:                          |  | Power over Ethernet            | IEEE 802.3af  |
| Multicast compliant                | yes  | Protection rating              | IP66  |
| Motion detector                    | yes  | Supply voltage                 | 12VDC, PoE  |
| Analysis functions                 | activity detection, motion analysis, tampering protection, Trip wire plus object counting, loitering detection, intrusion, Human detector, Defog | Temperature range (operation)  | -20°C ~ +50°C   |
| Alarm processing                   | recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out  | Text display                   | supplied  |
| Audio                              | 2 Way Audio  | Vandalism resistant            | yes   |
| Audio support                      | yes  | Certificates                   | IK10  |
| Password protection                | yes  | Scope of delivery:             |   |
| Internal storage                   | microSD card, microSDXC card   | Parts supplied                 | manual, eneo Site Manager, bag of screws  |
| Menu languages                     | English, German, French, Russian, Chinese, Korean, Japanese  |                                |   |

## Related Products



PS12DC-11|SKU: 218653



AK-8B|SKU: 225729



AK-9B|SKU: 225730

## Product recommendations



IAR-75E1024MMA|SKU: 214460



IAM-55E1008MUA|SKU: 214459



IAD-55G1004MUA|SKU: 216469



IAD-55G1008MUA|SKU: 216472




IAR-75G1008MMA|SKU: 216473



IAR-75G1016MMA|SKU: 216474



IAR-75G1024MMA|SKU: 216682



eneo Site Manager|SKU: 218218

