


HD ANALOG IR DOME CAMERA FIXED LENS

DI-350A28



| | |
|------------------------|---|
| MODEL | DI-350A28 |
| Image Sensor | 1/2.7" CMOS |
| Image Format | 5MP - 4:3 / 4MP - 16:9 |
| Effective Pixels | 2592(H)×1944(V) |
| Scanning System | Progressive |
| Resolution | 5MP: 2592x1944 @ 20FPS, 4MP: 2560x1440 @25/30FPS |
| Min. Illumination | 0.01Lux (0 Lux with IR on) |
| Day & Night | True Day&Night (ICR) |
| IR LED | 2 LED Array (20m) |
| OSD Menu | Available via CoC Only |
| CoC Support | Yes |
| Day & Night Mode | EXT, Color, B&W, Auto |
| Backlight Compensation | Off / BLC |
| S/N Ratio | ≥35dB (AGC Off) |
| White Balance | ATW, Manual |
| Noise Reduce | 2D-DNR |
| Video Output | 5MP / 4MP (Selectable by OSD Menu) AHD/TVI/CVI (4MP Only)/ CVBS + PAL/NTSC (Selectable by DIP Switch on cable) |
| Defog | Not Available |
| Privacy Mask | Not Available |
| Motion Detection | Not Available |
| D-Effect | Mirror |
| Lens (Field of View) | 2.8mm (92°) |
| Power | DC12V±10%, ~280mA |
| Operation Temp. | -30°C~+50°C |
| Waterproof | IP66 |
| Dimension | 104*82*93.2mm |
| Net weight | 270g |

Main Features:

Sensor: 1/2.7", 5 Mega-Pixel

Selectable Output:

5MP: AHD / TVI

4MP: AHD / CVI / TVI

CVBS

PAL/NTSC

Lens: 3.6mm Mega-Pixel Fixed

True Day & Night – ICR

IR Range: 20m (2 Array LED)




IP66

CoC Support

Weight: 270g



Junction Box (PR-B37JB)
is available



DIP Switch for Output Selection