

2MP 30x optische zoom IR camera




HD-SDI
EX-SDI



Eigenschappen

- 1/3" 2MP Panasonic CMOS sensor
- 1080p@60/50fps, 1080p@30/25fps, 720p@60/50fps, 720p@30/25fps
- HD-SDI, EX-SDI, CVBS
- x30 Optical Zoom(4.3mm~129mm) & x32 Digital Zoom
- IR LED 9pcs(Up to 100m)
- Real-time True WDR
- Digital Noise Reduction(2D+3D)
- Digital Slow Shutter
- Digital Image Stabilizer
- Privacy Mask Function
- High Light Compensation
- Defog Function
- ACE(Digital WDR)
- Motion Detection

Afmetingen (mm):



CAMERA	
Image Sensor	1/3" Panasonic CMOS Sensor
Total Pixels	1956 (H) x 1266 (V) = 2.48M Pixels
Active Pixels	1944 (H) x 1092 (V) = 2.12M Pixels
Video Format	1080p@60/50fps, 1080p@30/25fps, 720p@60/50fps, 720p@30/25fps
Min. Illumination	Color(1/30s) : 0.5 lux , BW(1/30s) : 0.1lux / 0lux(with IR LEDs) Color DSS(1/7.5s) : 0.125 lux , BW DSS(1/7.5s) : 0.025 lux / 0lux(with IR LEDs)
S/N Ratio	more than 50dB (AGC off)
Video Output	HD-SDI, EX-SDI, CVBS (service)

LENS	x30			x20			
	Lens Type	30x Day & Night Zoom Lens			20x Day & Night Zoom Lens		
Zoom Ratio	Optical x30, Digital x32 Zoom			Optical x20, Digital x32 Zoom			
Focal Length	f = 4.3 mm ~ 129.0 mm			f = 4.7 mm ~ 94.0 mm			
Aperture Ratio	F1.6 (wide) ~ F4.7 (tele)			F1.6 (wide) ~ F3.5 (tele)			
Angle Of View (D, H, V)	WIDE	71.3°	58.9°	45.3°	62.7°	55.4°	32.6°
	TELE	2.58°	2.11°	1.61°	3.3°	2.9°	1.6°

CAMERA FUNCTIES	
Camera Title	ID / Title / Zoom Ratio / System Message
Day & Night	Auto / Day / Night / Ext-in
WDR/BLC	OFF / WDR / BLC / HLC
ACE	Off / Low / Middle / High
DNR	Auto / Off / Low / Middle / High
Defog	Off / On(Auto / Manual)
Digital Image Stabilizer	Off / On
Motion Detection	Off / On (3 positions)
Privacy Mask	Off / On (24 positions)
Digital Slow Shutter	Off /x2 /x4
Gain Control	Off / On
White Balance	Auto / One Push / Manual / Indoor / Outdoor
Shutter Speed	1/30(25) ~ 1/30,000 sec
E.Zoom	Off / x2 ~ x32
Digital Flip	Off / H / V / H&V
Digital I/O	1 input / 2 output
Remote Control Interface	RS-422, 485
Protocol	Pelco-D / Pelco-P / WONWOO

ALGEMEEN	
Power Source	24Vac / 12Vdc
Power Consumption	1.5A(24Vac) / 2A(12Vdc)
Operating Temperature	-20°C~50°C /90% RH
Ingress Protection	IP67/IK10
Material	Aluminum / PC
Dimensions	136(W) x 78(H) X 134(D)
Weight	1.4kg

Accessoire:

VRC-300 (remote controller):

