



IPB-62M2712M5A

Article number: 227060

1/2,8" Network Camera, 1920x1080, Day&Night, DOL-WDR, 2,7-12mm, Infrared, IP66

1/2.8" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 1920x1080 (Full HD)	Triple Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 2,7~12mm	Responsive Web Design, Zero Configuration
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE or 12VDC
Motion Detection, Privacy Zones, Defog	For outdoor use IP66
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

Camera:		Features:	
Camera type	Bullet	Privacy zones masking	Areas-ON/OFF switchable
Sensor size	1/2,8"	Remote configuration	web browser
Resolution standard	HD 1080p	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Imager	CMOS, Sony STARVIS, Sensor IMX307	User interface	Type A (orange / grey)
System	True Day&Night	Mirror function	mirror, flip
Sensitivity	0,06 Lux, at F1.3, 40IRE	Digital Noise Reduction (DNR)	yes
Low speed shutter	yes, 1x~10x	Network:	
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	Interfaces / Inputs / Outputs:	
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR	Video outputs	no
Flickerless function	yes	External connections	RJ-45, 12VDC input (DC plug)
Backlight compensation	BLC, HLC	Ethernet interface	10Base-T, 100Base-TX
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)	Alarm inputs	no
IR cut filter	switchable	Alarm outputs	no
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes	Serial interfaces	Ethernet
Signal-to-noise ratio	50dB	General:	
Video:		Series	eneo LN-Series
Resolution	1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Dimensions (HxWxD)	78,5x78,5x214mm
Resolution max.	1920x1080	Illumination	infrared, 4x High Power LEDs 850nm
Image display	VerticalView 90°/270°, 4:3, 16:9	Illumination range	approx. 40m
Stream types	Multi Streaming	Colour (housing)	Pantone Cool Gray 1C
Image transmission rate max.	30 fps	Housing	outdoor
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG	Housing material	aluminium, plastic
Lens:		Weight	520g
Lens type	Varifocal (motorized)	Integrated wall mount	yes
Zoom factor	4x	Power consumption	8,5W
Focal length	2,7 - 12 mm	Blower	yes
Digital zoom	yes	Mounting	wall mount, ceiling mount
MOD (Minimum object distance)	0,5 m	ONVIF	ONVIF Profile S, ONVIF Profile T
Iris control	DC	Power over Ethernet	IEEE 802.3af
Vertical angle of view	54 - 18 °	Window heater	no
Horizontal angle of view	103 - 33 °	Protection rating	IP66
Features:		SDK	upon request
Multicast compliant	yes	Hidden cable management	yes
Motion detector	yes	Sunshield	yes
Analysis functions	motion detection, Defog	Supply voltage	12VDC, PoE
Alarm processing	E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping	Temperature range (operation)	-20°C ~ +50°C
Audio support	no	Text display	supplied
Password protection	yes	Vandalism resistant	no
e-PTZ support	yes	Scope of delivery:	
Internal storage	no	Parts supplied	manual, bag of screws
Menu languages	English, German, French, Korean		


Product recommendations



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472



eneo Site Manager | SKU: 218218

