



IPD-75A2713M5A

Article number: 227052

1/2,8" Network Dome, Fix, 2592x1944, Day&Night, DOL-WDR, 2,7-13,5mm, Infrared, IP67

1/2.8" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 2592x1944, 5 Megapixel	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 2,7~13.5mm	Micro SD Card, HTML5 replay, Audio, Alarm
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE, 12VDC or 24VAC
VCA (Video Content Analysis), ONVIF event mapping	For outdoor use IP66, vandal proofed IK10
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

Camera:	
Camera type	Dome
Sensor size	1/2.8"
Resolution standard	5 Megapixel
Imager	CMOS, Sony STARVIS, Sensor IMX335
System	True Day&Night
Sensitivity	0,05 Lux, at F1.6, 40IRE
Low speed shutter	yes, 1x-10x
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR
Flickerless function	yes
Backlight compensation	BLC, HLC
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)
IR cut filter	switchable
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes
Signal-to-noise ratio	50dB

Video:	
Resolution	2592x1944 (4:3), 2592x1520 (16:9), 2560x1440 (16:9), 1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)
Resolution max.	2592x1944
Image display	VerticalView 90°/270°, 4:3, 16:9
Stream types	Multi Streaming
Image transmission rate max.	30 fps
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG

Lens:	
Lens type	Varifocal (motorized)
Zoom factor	4x
Focal length	2,7 - 13,5 mm
Digital zoom	yes
MOD (Minimum object distance)	0,5 m
Iris control	DC
Vertical angle of view	54 - 17 °
Horizontal angle of view	97 - 29 °

Features:	
Multicast compliant	yes
Motion detector	yes
Analysis functions	motion detection, Field detection, Defog, Line detection
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out
Vertical tilt range	65 °(25 ~ 90°)
Audio	2 Way Audio
Audio support	yes
Password protection	yes

Features:	
e-PTZ support	yes
Internal storage	microSDHC card, microSDXC card
Menu languages	English, German, French, Korean
Privacy zones masking	Areas-ON/OFF switchable
Remote configuration	web browser
Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
User interface	Type A (orange / grey)
Mirror function	mirror, flip
Digital Noise Reduction (DNR)	yes

Network:	
Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour

Interfaces / Inputs / Outputs:	
Video outputs	no
External connections	micro SD card slot, alarm in/output, RJ-45, Combi connector, connection cable approx.15cm
Ethernet interface	10Base-T, 100Base-TX
Alarm inputs	1
Alarm outputs	1
Serial interfaces	Ethernet

General:	
Series	eneo Callisto, eneo LN-Series
Dimensions (HxWxD)	72x74x125mm
Illumination	infrared, 2x High Power LEDs 850nm
Illumination range	approx. 40m
Colour (housing)	Pantone Cool Gray 1C
Colour (bubble)	clear
Housing	outdoor, indoor
Housing material	aluminium
Weight	1 kg
Heater	no
Power consumption	10,8W
Blower	yes
Mounting	wall mount, ceiling mount
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection rating	IP67
SDK	upon request
Supply voltage	12VDC, 24VAC, PoE
Temperature range (operation)	-50°C ~ +50°C
Text display	supplied
Vandalism resistant	yes
Certificates	IK10

Scope of delivery:	
Parts supplied	manual, bag of screws

Related Products



DOME/WEDGE2 | SKU: 207192



DOME/BASIS1 | SKU: 209831



AK-5 | SKU: 209832



DOME-WB1+DOME/ Basis1 | SKU: 209880



Callisto TB | SKU: 212519


Product recommendations



IAD-55G1004MUA | SKU: 216469



IAD-55G1008MUA | SKU: 216472



eneo Site Manager | SKU: 218218



IAM-4MU1001M0A | SKU: 221334

