



IPD-68M3611P5A

Article number: 227050

1/2,5" Network Dome, Fix, 3840x2160, Day&Night, DOL-WDR, 3,6-11mm, Infrared, Indoor

1/2.5" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 3840x2160, 8 Megapixel	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 3.6~11mm	Slot for Micro SD Card, HTML5 replay
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE or 12VDC
VCA video analysis, ONVIF event mapping	Wedge adapter included (10° inclination)
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

Camera:	
Camera type	Dome
Sensor size	1/2.5"
Resolution standard	8 Megapixel
Imager	CMOS, Sony STARVIS, Sensor IMX274
System	True Day&Night
Sensitivity	0,2 Lux, at F1.5, 40IRE
Low speed shutter	yes, 1x-10x
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR
Flickerless function	yes
Backlight compensation	BLC, HLC
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)
IR cut filter	switchable
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes
Signal-to-noise ratio	50dB

Video:	
Resolution	3840x2160 (16:9), 2592x1520 (16:9), 1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)
Resolution max.	3840x2160
Stream types	Multi Streaming
Image transmission rate max.	30 fps
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG

Lens:	
Lens type	Varifocal (motorized)
Zoom factor	3x
Focal length	3,6 - 11 mm
Digital zoom	yes
MOD (Minimum object distance)	0,5 m
Iris control	DC
Vertical angle of view	46 - 21 °
Horizontal angle of view	84 - 40 °

Features:	
Multicast compliant	yes
Motion detector	yes
Analysis functions	motion detection, Field detection, Defog, Line detection
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping
Vertical tilt range	+/-60°
Audio support	no
Password protection	yes
e-PTZ support	yes

Features:	
Internal storage	microSDHC card, microSDXC card
Menu languages	English, German, French, Korean
Privacy zones masking	Areas-ON/OFF switchable
Remote configuration	web browser
Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
User interface	Type A (orange / grey)
Mirror function	mirror, flip
Digital Noise Reduction (DNR)	yes

Network:	
Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour

Interfaces / Inputs / Outputs:	
Video outputs	no
External connections	RJ-45, 12VDC input (DC plug), connection cable approx.55cm
Ethernet interface	10Base-T, 100Base-TX
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Ethernet

General:	
Series	eneo Callisto Indoor, eneo LN-Series
Dimensions (HxWxD)	94x116mm
Illumination	infrared, 2x High Power LEDs 850nm
Illumination range	approx. 30m
Colour (housing)	white
Colour (bubble)	clear
Housing	indoor
Housing material	plastic
Weight	300g
Heater	no
Power consumption	8,5W
Blower	yes
Mounting	wall mount, ceiling mount
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
SDK	upon request
Supply voltage	12VDC, PoE
Temperature range (operation)	-10°C ~ +50°C
Text display	supplied
Vandalism resistant	yes

Scope of delivery:	
Parts supplied	manual, bag of screws


Product recommendations



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472



eneo Site Manager | SKU: 218218

