



IPD-78M3611M5A

Article number: 220930

1/2,5" Network Dome, Fix, 3840x2160, Day&Night, DOL-WDR 3,6-11mm, Infrared, IP67

1/2.5" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 3840x2160, 8 Megapixel	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 3,6-11mm	Slot for Micro SD Card, HTML5 replay, Audio, Alarm
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE, 12VDC or 24VAC
VCA video analysis, ONVIF event mapping	For outdoor use IP66, vandal proofed IK10
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

Camera:		Features:	
Camera type	Dome	Internal storage	microSDHC card, microSDXC card
Sensor size	1/2.5"	Menu languages	English, German, French, Korean
Resolution standard	8 Megapixel	Privacy zones masking	Areas-ON/OFF switchable
Imager	CMOS, Sony STARVIS, Sensor IMX274	Remote configuration	web browser
System	True Day&Night	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Sensitivity	0,2 Lux, at F1.5, 40IRE	User interface	Type A (orange / grey)
Low speed shutter	yes, 1x-10x	Mirror function	mirror, flip
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.	Digital Noise Reduction (DNR)	yes
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	Network:	
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Flickerless function	yes	Interfaces / Inputs / Outputs:	
Backlight compensation	BLC, HLC	Video outputs	no
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)	External connections	micro SD card slot, alarm in/output, RJ-45, Combi connector, connection cable approx.15cm
IR cut filter	switchable	Ethernet interface	10Base-T, 100Base-TX
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes	Alarm inputs	1
Signal-to-noise ratio	50dB	Alarm outputs	1
		Serial interfaces	Ethernet
Video:		General:	
Resolution	3840x2160 (16:9), 2592x1520 (16:9), 1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Series	eneo Callisto, eneo LN-Series
Resolution max.	3840x2160	Dimensions (HxWxD)	72x74x125mm
Stream types	Multi Streaming	Illumination	infrared, 2x High Power LEDs 850nm
Image transmission rate max.	30 fps	Illumination range	approx. 40m
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG	Colour (housing)	Pantone Cool Gray 1C
		Colour (bubble)	clear
Lens:		Housing	outdoor, indoor
Lens type	Varifocal (motorized)	Housing material	aluminium
Zoom factor	3x	Weight	1 kg
Focal length	3,6 - 11 mm	Heater	no
Digital zoom	yes	Power consumption	10,8W
MOD (Minimum object distance)	0,5 m	Blower	yes
Iris control	DC	Mounting	wall mount, ceiling mount
Vertical angle of view	46 - 21 °	ONVIF	ONVIF Profile S, ONVIF Profile T
Horizontal angle of view	84 - 40 °	Power over Ethernet	IEEE 802.3af
Features:		Protection rating	IP67
Multicast compliant	yes	SDK	upon request
Motion detector	yes	Supply voltage	12VDC, 24VAC, PoE
Analysis functions	motion detection, Field detection, Defog, Line detection	Temperature range (operation)	-50°C ~ +50°C
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out	Text display	supplied
Vertical tilt range	65 °(25 ~ 90°)	Vandalism resistant	yes
Audio	2 Way Audio	Certificates	IK10
Audio support	yes	Scope of delivery:	
Password protection	yes	Parts supplied	manual, bag of screws
e-PTZ support	yes		

Related Products



DOME/WEDGE2 | SKU: 207192



DOME/BASIS1 | SKU: 209831



AK-5 | SKU: 209832



DOME-WB1+DOME/ Basis1 | SKU: 209880



Callisto TB | SKU: 212519


Product recommendations



IAD-55G1004MUA | SKU: 216469



IAD-55G1008MUA | SKU: 216472



eneo Site Manager | SKU: 218218



IAM-4MU1001M0A | SKU: 221334

