



IAR-7SG1008MMB

Article number: 226921

Gigabit Switch, Managed, 135W, 8x PoE, 2x SFP, 2x RJ45, 10/100/1000 Mbps, 19", 1 HE

PoE Switch, Rack Montage	Web configuration, Web management
Gigabit Uplink Ports: 2x RJ45, 2x SFP	VLAN, PoE management, MAC address table
8x 10/100/1000 PoE Ports, IEEE 802.3af/at	Port mirroring, password, PoE Budget LED Display
Up to 30W per port, Total ≤135W	CCTV mode allows transmission up to 250m @ 10Mbps
ESD protection IEC61000-4-5 standard	Temperature range -10°C ~ +50°C
Managed L2 switch, Built in low-noise fans	Rack mounting brackets included

Specifications

Features:	
Multicast compliant	yes
Port mirror	yes
Security	Password protection, Fast-Ring, Port Isolation, Port speed setup, Radius Authentication
Network:	
Network protocols	RSTP, FTP, TFTP, HTTP, IGMP, SNMPV1, SNMPV2, SNMPV3, QoS
Ethernet Standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX, IEEE 802.3x Flow Control, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE), IEEE 802.3ad Link Aggregation Control Protocol, IEEE 802.1Q VLAN, IEEE 802.1D Spanning Tree Protocol, IEEE 802.1x Radius network access control
Internal switching capacity (Mpps)	17,9 Mpps
Internal switching capacity (Gbit/s)	24 Gbps
VLAN	yes
Interfaces / Inputs / Outputs:	
Ports	8x 10/100/1000Base-T, 2x 1000Base-T SFP, 2x 10/100/1000Base-TX, Console RJ45-RS232
General:	
Dimensions (HxWxD)	44,5x442x194,5mm
Number PoE ports	8
Type	Layer2 switch
Weight	1,5 kg
Power consumption	150W
Blower	no
Management	yes
Mounting	19" rack
PoE Power	135 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Temperature range (operation)	-10°C ~ +45°C
Scope of delivery:	
Parts supplied	manual, power cord, 19" rack mount angle
Notes:	
ESD	Contact discharge 6KV, Air discharge 8KV, IEC61000-4-2, IEC61000-4-5

Product recommendations



SFP-1310S40|SKU: 216477



SFP-1310M40|SKU: 216478



SFP-0850M10|SKU: 216479



SFP-1310S10|SKU: 216566



SFP-0850M40|SKU: 218758



RJT-1000SFP|SKU: 219525

