



IEB-54F0028M0A

Article number: 225714

1/3" Network Camera, Day&Night, 2592x1520, H.265, Infrared, 2.8mm, PoE, IP66

1/3" Omnivision CMOS sensor	ROI (Region of interest) Hi-Stream to reduce the bandwidth
Fixed 2.8mm, Day&Night lens	
Resolution max. 2592x1520	Tampering, Defog
Compression H.265/ H.264/ MJPEG	D-WDR (Digital Wide Dynamic Range)
Cross-Web-Browsing	Framerate increase on motion detection
	Compact design, Outdoor applications, IP66

Specifications

Camera:		Features:	
Camera type	Bullet	Remote configuration	web browser
Sensor size	1/3"	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
Resolution standard	4 Megapixel	User interface	Type B (white / blue)
Imager	CMOS, OmniVision Sensor 4689	Mirror function	H-flip, mirror
System	True Day&Night	Digital Noise Reduction (DNR)	yes
Sensitivity	0,1 Lux, 50 IRE	Network:	
Low speed shutter	yes, automatic	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS, OpenVPN
Manual electronic shutter (MES)	1~1/20.000sec.	Interfaces / Inputs / Outputs:	
Automatic electronic shutter (ESC)	1~1/20.000sec.	Video outputs	no
Wide Dynamic Range (WDR)	D-WDR	External connections	RJ-45, 12VDC input (DC plug), connection cable approx.40cm
Backlight compensation	BLC	Ethernet interface	10Base-T, 100Base-TX
Day/Night switching	day, night, auto	Alarm inputs	no
IR cut filter	switchable	Alarm outputs	no
White balance	automatic, manual	Serial interfaces	Ethernet
Signal-to-noise ratio	50dB	General:	
Video:		Series	eneo EN-Series, Safe & Easy
Resolution	2 Megapixel Modus @ 30fps, 4 Megapixel Mode @20fps, 2592x1520 (16:9), 1920x1080 (16:9), 1280x1024 (5:4), 1280x720 (16:9), 1024x768 (4:3), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 320x240 (4:3)	Dimensions (HxWxD)	76,6x75,8x150,4mm
Resolution max.	2592x1520	Illumination	infrared, 1x High Power LED 850nm
Image display	VerticalView 90°/270°, 4:3, 16:9, 5:4	Illumination range	approx. 30m
Stream types	1x H.265, 1x H.264, 1x MJPEG multiple	Colour (housing)	white
Image transmission rate max.	30 fps	Housing	outdoor
Compression standard	H.264, H.265, H.264+ (Smart Stream), H.265+ (Smart Stream), M-JPEG	Housing material	aluminium
Lens:		Weight	465g
Lens type	fixed focal length	Integrated wall mount	yes
Focal length	2,8 mm	Power consumption	5,1W
MOD (Minimum object distance)	0,3 m	Blower	no
Iris control	DC	Mounting	wall mount, ceiling mount
Vertical angle of view	52 °	ONVIF	ONVIF Profile S
Horizontal angle of view	93 °	Power over Ethernet	IEEE 802.3af
Features:		Window heater	no
Multicast compliant	yes	Protection rating	IP66
Motion detector	yes	SDK	upon request
Analysis functions	motion analysis, intrusion, tampering protection, Defog	Hidden cable management	yes
Alarm processing	E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML	Sunshield	no
Audio support	no	Supply voltage	PoE, 12VDC
Password protection	yes	Temperature range (operation)	-20°C - +50°C
e-PTZ support	yes	Text display	supplied
Internal storage	no	Vandalism resistant	no
Menu languages	English, German, French, Russian, Chinese, Korean, Japanese	Scope of delivery:	
Privacy zones masking	Areas-ON/OFF switchable	Parts supplied	manual, bag of screws

Related Products



AK-8B|SKU: 225729



AK-9B|SKU: 225730


Product recommendations



IAD-55G1004MUA|SKU: 216469



IAD-55G1008MUA|SKU: 216472



eneo Site Manager|SKU: 218218

