

## GD-ML-AP3230HD

81 cm (32") LCD/TFT Monitor LED 16:9



- Displays a full, flat 32" (81cm) diagonal image
- Designed for professional 24/7 usage
- LED Backpanel illumination
- Including IR Remote Control



### PROFESSIONAL

- Product Line Professional: These products cover most applications of modern video systems

## Specifications GD-ML-AP3230HD

### Monitor

LCD Panel size:	81.3 cm (32") Diagonal AM-TFT LED Backlight
Pixels - Total:	1920 (H) x 1080 (V)
Pixel Pitch:	0.36375 mm (H) x 0.36375 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	178° (H) ~ 178° (V)

### Video

Video Inputs:	1x Composite, BNC, Looped, 1x VGA, 2xHDMI
Video Standard:	PAL, NTSC
Brightness:	300 cd, m <sup>2</sup>
Contrast Ratio:	3000:1
Number of Colours:	16.7 million
Response Time:	6.5 ms

### General

Speakers:	2 x 2 W
OSD (On Screen Display):	Yes, multi language
Accessories included:	Power adapter, HDMI cable and remote control

### I/O Interface

Audio Inputs:	2 CH (1xHDMI, 1xMiniJack Connector)
Video Outputs:	1x CVBS (1 Vcc) BNC

### Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 100,000 hours

### Environmental

Operating Temperature:	0 °C ~ +40 °C
Humidity:	less than 90%, non condensing

### Electrical

Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	55 W

### Mechanical

Vesa Mount:	200 x 100 mm
Dimensions:	520 x 740 x 200 mm (20,5 x 29,1 x 7,9 inch)
Weight:	9000 g (19.8 lb)