

IAR-7SE1024MMB

SKU: 228222



Gigabit Switch, 24xPoE 100Mbps 2x RJ45 Gbit, 2xSFP Gbit, 390W, Managed, 19", 1HE

Main Features

PoE Switch, Rack Montage	Web configuration, Web management
Gigabit Uplink Ports: 2xRJ45, 2xSFP	VLAN, PoE management, MAC address table
24x 10/100 PoE Ports, IEEE 802.3af/at	Port mirroring, password
Up to 30W per port, Total ≤390W	Status LEDs
ESD protection IEC61000-4-5 standard	Temperature range -10 ° C ~ + 50 ° C
Managed L2 switch, Built in low-noise fans	Rack mounting brackets included

Specifications

Functions:	
Multicast compliant	yes
Port mirror	yes
QoS	yes
SNMP	yes
Security	Password protection, Fast-Ring, Port Isolation, Port speed setup, Radius Authentication
Network:	
Network protocols	RSTP, FTP, TFTP, HTTP, IGMP, SNMPV1, SNMPV2, SNMPV3, QoS
Ethernet standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX, IEEE 802.3x Flow Control, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE), IEEE 802.1Q VLAN, IEEE 802.1D Spanning Tree Protocol, IEEE 802.1p Quality of Service, IEEE 802.1x Radius network access control

IAR-7SE1024MMB

Continuation of the specifications

Internal switching capacity (Mpps)	9,5 Mpps
Internal switching capacity (Gbit/s)	12,8 Gbps
VLAN	yes
Interfaces / Inputs/ Outputs:	
Ethernet interface	10Base-T,100Base-TX,1000Base-T
Ports	24x 10/100Base-TX,2x 10/100/1000T SFP,2x 10/100/1000Base-TX,Console RJ45-RS232
Optical connector	SFP Port
General:	
Dimensions (HxWxD)	44,5x442x263mm
Weight	3.8kg
PoE ports (number)	24
Model	Rackmontage
Type	Layer2 switch
Power consumption	450W
Blower	yes
Management	yes
Mounting	19" rack
PoE budget	390 W
Power over Ethernet	IEEE 802.3af,IEEE 802.3at
Supply voltage	100~240VAC
Operating temperature	-10°C ~ +50°C
Application	indoor
Trunk	Contact discharge 6KV,Air discharge 8KV,IEC61000-4-2,IEC61000-4-5
Parts supplied:	
Parts supplied	manual,power cord,19" rack mount angle

Optional Accessory

SKU	Name	Description
219525	RJT-1000SFP	RJ45- SFP Transceiver Modul, 1000Base-T, 0°~+70°C
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

IAR-7SE1024MMB

Continuation of accessory



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

