

MEB-62V2713P0A

SKU: 233016



1/2.8" HD Bullet, Day&Night, 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, IP66

Abb. ähnlich

Main Features

1/2.8" 2.3 Megapixel progressive scan CMOS sensor

Compact housing for outdoor use

Resolution max. 1920x1080 (Full HD)

Multisignal: HD-TVI, AHD, CVI, Composite selectable

Variofocal 2.8~12mm day&night lens

LSC (Lens shading compensation)

Removable infrared cut filter

3D-DNR noise reduction

Digital Wide Dynamic Range (D-WDR)

Integral motion detection

4x High Power LED

Specifications

Camera:	
Camera type	Bullet
Sensor size	1/2.8"
Resolution Pixels	960x576, 1920x1080
Imager	CMOS, Sony, Sensor IMX323
System	True Day&Night
Sensitivity	0,3 Lux, at F1.6,40IRE
Low Speed Shutter	yes
Low speed shutter	automatic
Manual electronic shutter (MES)	1/25 ~ 1/50.000sec.
Automatic electronic shutter (ESC)	1/25 ~ 1/50.000sec..

MEB-62V2713P0A

Continuation of the specifications

Wide Dynamic Range (WDR)	D-WDR
Flickerless function	yes
Backlight Compensation	BLC,HLC
Day&Night switch	ICR
White balance	ATW,AWB,manual,outdoor,indoor,AWC
Signal-to-noise ratio	52db
Video:	
Signal format	Composite (FBAS),HD-TVI @ 2MP,AHD @ 2MP,CVI @ 2MP
Frame rate	25/30fps @ 1920x1080p
Synchronization	internal
Lens:	
Lens Type	Varifocal
Zoom Factor	4x
Focal Length	2,7 - 13,5 mm
Digital Zoom	no
MOD (Minimum Object Distance)	0,5 m
Aperture range (F)	F1.6
Iris Control	DC
Vertical Angle of View	49 - 15°
Horizontal Angle of View	95 - 27°
Video standard	PAL/NTSC
DORI:	
Detect (25px/m)	44 - 198 m
Observe (62 px/m)	16,6 - 80,5 m
Recognize (125 px/m)	8,2 - 40,1 m
Identify (250 px/m)	3,9 - 20,1 m
Functions:	
Motion Detector	yes
Analysis functions	Defog
OSD function control	OSD camera setup
Menu languages	German,English,French,Italian,Spanish,Turkish,Dutch,Portugese,Polish,Chinese,Russian
Privacy zone masking	Areas-ON/OFF switchable
Mirror function	rotation,mirror,V flip
Digital Noise Reduction	yes
Interfaces / Inputs/ Outputs:	
Video outputs	HD-TVI,AHD,CVI,composite (CVBS)
External connectors	video (BNC),12VDC power input,connection cable approx.40cm
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)

MEB-62V2713P0A

Continuation of the specifications

Serial interfaces protocols	UTC (HD-Signal Format)
General:	
Dimensions (HxWxD)	78,5x78,5x214mm
Weight	520g
Illumination	infrared
Illumination	4x High Power LEDs 850nm
Illumination range	approx. 30m
Color (housing)	Pantone Cool Gray 1C
Housing	outdoor
Housing material	aluminium,plastic
Integrated wall mount	yes
Power consumption	6.5W
Mounting	wall mount,ceiling mount
Protection rating	IP66
Sunshield	yes
Supply voltage	12VDC
Operating temperature	-20°C ~ +50°C
Text display	supplied
Parts supplied:	
Parts supplied	manual,drilling template,bag of screws
Remarks	NDAA compliance under Section 889, Part A.

Optional Accessory

SKU	Name	Description
230863	AK-10	Camera junction box for wall and ceiling mounting
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
225135	MAM-5MM2001M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

