

VSC-6302P

H-Bird Camera



▲ VSC-6302P

[Features]

- SONY 1/3" Super HADII High Sensitivity Color CCD
- High Resolution : 600TVL
- Min. Illumination : 0.15Lux
- Digital Day & Night for surveillance 24 hours
- DNR for saving storage
- Digital WDR (Wide Dynamic Range)
- Private Masking (8 zones)
- Motion Detection
- OSD for user convenience
- Gamma for adjustment can be select
- Mirror Function

[Specifications]

ITEM	VSC-6302P
Power Consumption	12VDC Only (Max.130mA)
	24VAC/12VDC (Max.180mA/Max.260mA)
	230VAC (Max.4.5watt)
Total Pixels	NTSC : 811(H) x 508(V), PAL : 795(H) x 596(V)
Effective Pixels	NTSC : 768(H) x 494(V), PAL : 752(H) x 582(V)
Size	SONY 1/3" Super HADII High Sensitivity Color CCD
Scanning System	2:1 Interlace
Synchronisation	INT
Frequency	NTSC : Horizontal:15.734 KHz Vertical :59.94 Hz PAL : Horizontal: 15.625 KHz Vertical : 50.00 Hz
Resolution	600 TV lines (Color), 700 TV lines (B/W)
Video Output	NTSC : 1.0Vp-p/75(V) Video 0.714Vp-p Sync 0.286Vp-p PAL : 1.0Vp-p/75 (Video 0.7 Vp-p Sync 0.3 Vp-p)
S/N (Y signal)	50dB (AGC Off)
Min. Illumination	0.15Lux 40IRE/F1.2 (Color), 0.01Lux 40IRE/F1.2 (B/W)
Color	COLOR / AUTO / BW
White Balance	ATW1 / ATW2 / AWC / MANUAL (2,300K~11,500K)
Electronic Shutter Speed	NTSC : AUTO / MANUAL(1/60~1/100,000) PAL : AUTO / MANUAL(1/50~1/100,000)
O.S.D	Built-in
Motion Detection	ON / OFF (64 Programmable Zones)
BLC	ON / OFF (64 Programmable Zones)
Mirror	Built-in (Horizontal Image Inversion)
Privacy Function	ON / OFF (8 Programmable Zones)
Iris Control	DC / VIDEO
Lens Mount	C/CS Mount (Screw Lock)
Operating Temperature /Humidity	-10°C ~ +50°C / 30~90% RH