

GRH-K1004A

4 Channel H.264 GDI Recorder with DVD-RW Drive



- 4 Channel FullHD 60fps recording capability (120fps live)
- supports up to 64TB with GDS-R04A or up to 16TB intern or eSATA
- Search by time, calendar, event or thumbnails
- USB2.0 Interface / eSATA Interface / Built in DVD-RW drive
- Compatible with Grundig CCTV Software
- Compatible to French law of August 2007 for quality in CCTV applications
- Compatible with many mobile applications such as iPhone®, Blackberry®, Android® and Windows Mobile®

SUMMARY


Based on the Television Standard for FullHD Television, GRUNDIG DIGITAL IMAGE (GDI) products feature up to 2 Megapixel (1920x1080) pictures in real-time (30fps) transmitted over coax cabling. Get the advantages of IP technology without their drawbacks. Get 16:9 megapixel pictures without network configuration, bandwidth problems and network security risks. Use existing coax cables and only exchange the cameras and recorders. Get a "real" live picture and see the things that happen in the now, not a few seconds ago. Connect a monitor directly to a camera using only a GDI-to-HDMI converter.

GDI is easy to handle, easy to install and produces amazing high quality pictures.

SPECIFICATIONS

Operating System	Embedded OS
Video Inputs	4 CH HD-SDI, BNC
Video Outputs	1 VGA, 1 HDMI
Storage Max. Expansion	16TB (intern or eSATA), 64 TB (GDS-R04A)
Video Compression	H.264, JPEG
Recording Resolution	FullHD (1920x1080), HD(1280x720)
Recording Speed	60fps (FullHD), 120fps (HD)
Recording Mode	Continuous, Event Alarm, Motion, Video Loss, Schedule, Manual
Display Resolution	max. 1920 x 1080
Display Speed	120 fps
Internal Backup	Built in DVD-RW drive
External Backup	USB HDD, USB Memory, DVD-R, Network, eSATA
Search Mode	Date/Time, Event Alarm, Motion, Video Loss, Go First, Go Last, Search Backup
Motion Detection	On/ Off/ Area Setting
Event Source	Motion, Alarm, Text, Video Loss, System
Event Action	Pop-Up, Relay, E-Mail, FTP, Network, Buzzer, PTZ Preset
Audio Inputs	4 CH, RCA
Audio Outputs	1 CH, RCA
Alarm Inputs	4 contact input N/O or N/C
Alarm Outputs	4 Relay
Compliant	SMPTE-292/296M
Interfaces	2 port RS485, 1 port RS232, System Keyboard, 1 NAS, 1 Ethernet and 2 USB 2.0 ports
ATM/POS	Supports up to 16 ATM/POS with VSI-Pro Hydra Modules
Video Streaming	Versatile Triple Streaming (Dual H.264 + single JPEG)
Network	Ethernet, 10/100 Base-T for PC client, 1000 Base-T for storage, ADSL Static IP, ADSL Dynamic IP(PPPoE),Cable Network (Dynamic IP)
Client software	Windows (XP, Vista, 7), Web Viewer: IE, Firefox, Safari, Chrome; Mobile: iPhone (OS4), Blackberry, Android, Windows Mobile, Symbian
Time Setting	Setting by NTP Server local or internet
Multiplex Function	Pentaplex
Auto Switching	0, 3, 5, 10, 20, 30 sec, Event or manual
Supply Voltage	110 ~ 240 VAC/50Hz
Power Consumption	75 W
Weight	8.9 kg
Dimensions w*h*d	445 x 88 x 418 mm

DIMENSIONS



ACCESSORIES

GDS-R04A
External Storage



GSW-CMS
DVR Management Software



GTH-K001E
1Ch Repeater & 2 Ch Distributor

