

GTH-K0011E

1Ch HD-SDI Repeater & 2 Ch Distributor



- HD-SDI 1Ch repeater & 2 Ch Distributor
- Full HD, 1920 x 1080p, 25/30 fps
- Cascade up to 4 devices
- Automatic Re-clocking and Equalisation

SUMMARY

Based on the Television Standard for FullHD Television, HD-SDI products feature up to 2 Megapixel (1920x1080) pictures in real-time (30fps) transmitted over coax cabling.

Get the advantages of IP technology without their drawbacks. Get 16:9 megapixel pictures without network configuration, bandwidth problems and network security risks. Use existing coax cables and only exchange the cameras and recorders. Get a "real" live picture and see the things that happen in the now, not a few seconds ago. Connect a monitor directly to a camera using only a HD-SDI-to-HDMI converter.

HD-SDI products are easy to handle, easy to install and produce amazing high quality pictures.

SPECIFICATIONS

Video Inputs	1 CH HD-SDI, BNC
Video Outputs	2 CH HD-SDI, BNC
Video Resolution	1920 x 1080 (30/25 fps), 1280 X 720 (30/25 fps)
Max. Distance	up to 140m (RG59), up to 200m (RG6)
LED Indicator	Power, link
Compliant	SMPTE-292/296M
Operating Temperature	0°C ~ +50°C
Humidity	less than 90%
Supply Voltage	12 VDC (External Power Supply)
Power Consumption	3 W
Weight	0,12 kg
Dimensions w*h*d	91.06 x 26 x 64.3 mm

DIMENSIONS

